



**1178-VXL**

**1/2" VIBROTHERM DRIVE COMPOSITE IMPACT WRENCH**

**FEATURES**

- Provides 950 ft-lb maximum torque and 1,300 ft-lb of loosening torque
- VIBROTHERM DRIVE®; impact wrenches incorporate the new patented AIRCAT design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- The latest patented AIRCAT muffler system provides the AIRCAT's unmatched low noise levels (86 dBA)
- The patented grip design provides the customary AIRCAT® operator comfort

**SPECIFICATIONS**

Loosening Torque (ft-lb) @90psi	1300
Square Drive (in.)	1/2
Bolt Capacity (in.)	9/16
Free Speed (RPM)	7,500
Impacts Per Minute (IPM)	1,400
Weight (lbs.)	4.5
Length (in.)	6.4
Noise Level d(B)A	86
Vibration Level (m/sec <sup>2</sup> )	7.7
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4

**VIBROTHERM**  
by AIRCAT DRIVE®



**Styled for perfection and built to last!**

**AIRCAT**

a Division of Florida Pneumatic Manufacturing Corporation  
851 Jupiter Park Lane / Jupiter, Florida 33458

**www.AIRCAT.com**

**(800) 356-3392**