



1993-1-VXL

**1" VIBROTHERM DRIVE COMPOSITE STRAIGHT IMPACT
WRENCH**

FEATURES:

- Provides 2,100 ft-lb maximum torque and 2,300 ft-lb of loosening torque
- VIBROTHERM DRIVE® impact wrenches incorporates the new patented AIRCAT® design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- 6,000 RPM Free Speed
- Unmatched power-to-weight ratio
- Rubber handle grip and rubberized trigger inserts for ultimate comfort
- Combined friction-ring and through-hole socket retainer
- Investment in tooling, materials, and the triple injection molding processes enables AIRCAT® to produce cosmetic designs that are unmatched in the industry

SPECIFICATIONS

Square Drive (in.)	1
Air Cons. (CFM)	10
Bolt Capacity (in.)	1-1/4
Air Inlet (in.) NPT/BSP	1/2
Rec. Hose Size (in.)	1/2
Weight (lbs.)	18.5
Length (in.)	13.4
Free Speed (RPM)	6,000
Impacts Per Minute (IPM)	950
Max. Torque (ft-lb)	2,100

VIBROTHERM
by **AIRCAT. DRIVE®**



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com
(800) 356-3392