



1890-P

1" TWO JAW PISTOL GRIP IMPACT WRENCH

FEATURES

- Provides 2,000 ft-lb maximum torque and 2,500 ft-lb of loosening torque
- Two jaw clutch provides unparalleled torque output and increases the life of the hammer beyond other impact mechanisms
- The two jaw clutch does not waste energy. This combined with the precision air motor dramatically reduces air consumption over other 1" impact wrenches to 24.5 CFM free running and 6 average
- Designed for fleet and off road vehicle service and steel erection
- Steel hammer case and heavy duty cast housing handle provide ultimate reliability
- Combined through hole and friction ring socket retainer

SPECIFICATIONS

| | |
|--------------------------|-------|
| Square Drive (in.) | 1 |
| Air Cons. (CFM) | 6 |
| Bolt Capacity (in.) | 1-1/4 |
| Air Inlet (in.) NPT/BSP | 1/2 |
| Rec. Hose Size (in.) | 1/2 |
| Weight (lbs.) | 24 |
| Length (in.) | 11 |
| Free Speed (RPM) | 4,200 |
| Impacts Per Minute (IPM) | 1,200 |
| Max. Torque (ft-lb) | 2,000 |



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com

(800) 356-3392